

MACCROSSROAD 3.0 LOW META //



ART. NO. 67743

EN ISO 20345:2022 S3 M CI HI HRO SRC | EN ISO 20345:2022 S3L FO M CI HI HRO SC SR

SIZES 36 - 48

APPLICATIONS //

Utilities, construction and civil engineering, oil and gas, heavy industry, rail, ports, defense, agriculture and green spaces

TECHNICAL SPECIFICATIONS //

- **sole:** MACSOLE® ADVENTURE 3.0 rubber with MACABSORB insert in forefoot and heel for excellent shock absorption and flexibility, excellent levels of grip (SR), oil, hydrocarbon and chemical-resistant, resistance to contact heat up to 300°C (HRO) | ergonomic sole supports natural rolling movement of the foot, all-terrain sole profile disperses surface debris for better grip | rubber scuff protects leather prolonging product life
- **upper:** water-resistant full-grain leather | Agile Ankle Guard and reinforced heel supports foot for better stability especially on uneven surfaces while retaining a high level of movement
- **lining:** 3D mesh for better ventilation and fast drying
- **tongue:** gusset tongue made with synthetic and water-resistant textile to keep dirt and liquid out | very flexible 100 J metatarsal protection integrated within the tongue | loop holds tongue in place
- **ankle padding:** flexible and compact foam around ankle and Achilles tendon for protection and comfort
- **toe cap:** metal-free, lighter than steel, does not conduct heat and cold compared to a metal toe cap
- **penetration-resistant midsole:** metal-free, light and flexible, does not conduct heat and cold compared to a metal midsole, protects 100% of the surface of the foot
- **insole:** removable anatomically shaped with shock absorbers in the heel and forefoot | microfibre

top layer for better abrasion resistance and durability, very high moisture absorption capacity and fast drying | bottom layer made from 85% recycled open cell PU foam | washable at 30°C enhances hygiene

- **sizing system:** French (EU) | width 11
- **weight:** 680 g in size 42

GENERAL FEATURES //

- 100% metal-free
- free from harmful substances according to the uvex group's prohibited substances list, exceeding the requirements of the REACH regulations
- certified for use with the XSole connected sole for lone worker protection