MS 30 HIGH //

100 % metal free

Article ID : 67633
EN ISO 20345:2011 S3 HRO SRC | EN ISO 20345:2022 S3L FO HRO SR
Sizes : 36-48

APPLICATIONS //

logistics | transport | industry | services | public administration | craft industries | second fit trades | humid conditions

TECHNICAL SPECIFICATIONS //

- **sole**: MACSOLE® SPORT rubber | excellent levels of grip (SR) | oil, hydrocarbon & chemical-resistant | resistance to contact heat up to 300°C (HRO) | excellent grip qualities with its tread pattern that disperses surface debris & increases ground-bearing surfaces to reduce slip risk | antistatic
- **intermediate sole**: new MACFOAM technology in Phylon offering high performance shock absorption & cushioning | lightweight, flexible & durable, the sole performance will last the life of the shoe
- **upper**: water-resistant oiled leather & microfibre
- **lining**: 3D mesh polyester, excellent breathability & quick drying
- **tongue**: synthetic & textile | gussets help keep dirt & liquid out
- **ankle padding**: flexible & compact foam around ankle
- **toe cap**: metal-free | lighter than steel | does not conduct heat & cold compared to a metal toe cap
- **penetration-resistant midsole**: metal-free | light & flexible | does not conduct heat & cold compared to a metal sole | protects 100% of the surface of the foot
- **insole**: removable | textile top layer for better abrasion resistance, very high moisture absorption capacity & fast drying | bottom layer made from open cell foam | washable at 30°C enhances hygiene
- **size system**: French (EU) | width 11
- **weight**: 520 g in size 42

UVEX HECKEL s.a.s. | 44 rue d'Engwiller – La Walck | 67350 Val de Moder | France | **Telephone**: +33 (0)3 88 07 61 08
Fax: +33 (0)3 88 72 51 06 | **E-mail**: contact.export@uvex-heckel.fr | **Internet**: www.heckel.fr