

uvex Hand Protection System

uvex rubiflex S - NB40S

- Double dipped NBR (nitrile butadiene rubber) coated
- High flexibility
- Good abrasion resistance
- Good resistance to chemicals, fats, acids and mineral oils
- Cotton lining for superior water vapour absorption
- EN ISO 374-1:2016 (JKNOPT)
- EN 388:2016 (2121X)



EN ISO 374-1:2016/Type A



JKNOPT

EN 388:2016



2121X



MADE IN GERMANY

uvex Point of Difference	Benefits
High quality absorbent cotton liner	Exceptional comfort and sweat management
Pure Nitrile Butadiene rubber coating	High chemical resistance while maintaining excellent flexibility and comfort

Permeation resistance of type A: at least 30 minutes each with at least 6 test chemicals.

J - n-heptane level 6 > 480 minutes

K - Sodium hydroxide 40% level 6 > 480 minutes

N - Acetate acid 99% level 6 > 480 minutes

O - Ammonium hydroxide 25% level 5 > 240 minutes

P - Hydrogen peroxide 30% level 6 > 480 minutes

T - Formaldehyde 37% level 6 > 480 minutes

Target Applications (but not limited to):

- Petrochemical industry
 - handling petroleum products
- Petrochemical industry
 - handling alcohols
- Alumina refining
 - level 6 sodium hydroxide (caustic soda)
- Battery manufacturing
 - sulphuric acid (battery acid) level 6

Packaging:

NB40S

- 10 pairs per bundle
- 60 pairs per carton

Part Numbers & Barcodes:

NB40S

- size 8 - NB40SF1 - 9321123001189
- size 9 - NB40SF2 - 9321123001196
- size 10 - NB40SF3 - 9321123001202
- size 11 - NB40SF4 - 9321123001172