

uvex



Prescription Safety Eyewear

protecting people

SBU Occupational Health

uvex – a competent partner

uvex as a partner for individual protective equipment

Our eyesight needs special protection – and many activities in our working lives leave them vulnerable to serious risks. uvex does not compromise on eye protection and offers reliable protection with individually adapted safety spectacles.

Decades of experience and innovative technologies form the basis for uvex products, which are manufactured in accordance with the most stringent safety standards. In addition to safety, uvex also guarantees maximum comfort and quality. Protective equipment that fits properly not only offers reliable protection, but is more likely to be worn by the employee.

Our service – your benefits

uvex offers maximum service with maximum flexibility. Our specialists are happy to advise you with regard to professional and flexible solutions, tailored to the individual requirements of your company.

Our wide uvex collection enables us to find prescription safety spectacles for each of your employees.



Individual eye protection from uvex

Prescription safety spectacles protect the eyes, and improve the wearer's vision. uvex offers individual prescription safety spectacles for all areas of application.

- Prescription safety spectacles certified in accordance with EN 166
- A wide selection of focus types and lens materials to meet all requirements
- An extremely wide range of frames, cater for all employee facial shapes
- Qualified advice and individual adjustment from opticians



RX are produced locally

The individual PPE eyewear range from uvex provides exceptional quality and the latest technology. uvex innovations continue to set new standards in industrial health and safety.

- uvex's prescription safety eyewear is recognised for its exceptional wearer comfort, stylistic designs and sophisticated functionality.



Well-rounded professional expertise

Individual PPE products demand competent advisory expertise to guarantee the right solution and fit. For this reason, adjustments are carried out by qualified professionals.

Upon request, uvex can provide seminars for professional individuals (e.g. company doctors or occupational nurses) within companies to provide them with a level of knowledge about the adjustment of PPE products.

- Prescription PPE products for all employees
- Certified products create legal certainty
- Adjustments carried out by qualified specialists
- uvex academy: seminars/safety days

Prescription safety spectacles

Individual eye protection from uvex

**MADE FOR
YOUR EYES**
MADE IN UVEX



uvex prescription safety spectacles are individually adapted to the wearer's vision while offering the best possible protection in the workplace.

The spectacles are certified and marked in accordance with EN 166, so they can be used in workplaces where safety spectacles are mandatory. As occupational safety spectacles, they not only protect the eyes (from UV radiation, flying particles, dust etc.), but are also a visual aid because the lenses have a dioptric effect.

uvex offers a wide range of high-quality lens materials, focus types and frames. This makes it easier to switch between personal spectacles and employer-provided safety spectacles, which increases wearer acceptance.

The comprehensive uvex quality system guarantees the best design from an optical and processing technology perspective. All materials used (lenses, frames, cases etc.) are free from harmful substances and are regularly inspected.

The collection

uvex offers a variety of frames for prescription safety spectacles.

uvex RX bc plastic



- bc: basic collection
- in different shapes, sizes and colours

uvex RX bc metal



- bc: basic collection
- in different shapes, sizes and colours

uvex RX cb



- cb: custom bidge
- Suitable for people with:
- a flat nose bridge
 - high cheekbones
 - wide temples

uvex RX cd



- cd: comfort and design
- safety spectacles in a sporty design

uvex RX sp



- sp: sporty
- safety spectacles in a wrap-around design for anatomic sport lenses

uvex RX cd flip up



- cd: comfort and design
- for workplaces with special requirements

uvex RX cf



- cf: close fit
- safety spectacles with all-round protection and tailored to your individual prescription
- recommended for handling chemicals and/or working in dusty environments

uvex

Prescription safety spectacles

uvex RX bc plastic frames

Basic collection
uvex RX bc plastic

classic
timeless
virtually unrestricted prescription lenses



6109203



6109204

uvex RX bc 5503

- plastic frames with classic lens shape
- transparent side shields with integrated brow guard
- good fit with anatomically shaped nose bridge

uvex RX bc 5503		
Art. no.	6109203	6109204
Ref. no.	5503 1300 54/17	5503 7415 54/17
Lens diameter	54 mm	54 mm
Bridge width	17 mm	17 mm
Colour	anthracite	green, grey
Extras		metal arms with sprung hinges
Marking on frame	W 166 FT CE	W 166 FT CE



6108215



6109210

uvex RX bc 5502

- close-fitting plastic frames
- side shields and integrated brow guard frame design
- specially shaped frames provide protection against particles from below
- good fit with anatomically shaped nose bridge
- individually adjustable side arms with four different lengths and adjustable soft-form comfort ear pieces

uvex RX bc 5502	
Art. no.	6108215
Ref. no.	5502 1725 56/15
Lens diameter	56 mm
Bridge width	15 mm
Colour	grey
Marking on frame	W 166 FT CE

previously: uvex 9134 meteor

uvex RX bc 5506

- comfortable plastic frame
- side shields and integrated brow guard frame design
- good fit with anatomically shaped nose bridge

uvex RX bc 5506	
Art. no.	6109210
Ref. no.	5506 1725 56/18
Lens diameter	56 mm
Bridge width	18 mm
Colour	light grey, translucent
Marking on frame	W 166 FT CE

Prescription safety spectacles

uvex RX bc plastic frames



6109262



6109264



6109263



6109265



uvex RX bc 5527

- plastic frame in a retro design
- transparent frame with accent colour for an unrestricted field of vision
- good fit thanks to anatomically shaped nose area
- completely metal-free

uvex RX bc 5527

Art. no.	6109262	6109263	6109264	6109265
Ref. no.	5527 2939 53/18	5527 2915 53/18	5527 2927 57/18	5527 2915 57/18
Lens diameter	53 mm	53 mm	57 mm	57 mm
Bridge width	18 mm	18 mm	18 mm	18 mm
Colour	transparent, aubergine	transparent, grey	transparent, graphite	transparent, grey
Marking on frame	16321 W U1,2 G0 C 1-S/1-M CE	16321 W U1,2 G0 C 1-S/1-M CE	16321 W U1,2 G0 C 1-M/1-L CE	16321 W U1,2 G0 C 1-M/1-L CE



CO2 footprint:

0.42 kg CO₂ e 07/2025
(6109262, 6109263),

0.44 kg CO₂ e 07/2025
(6109264, 6109265),

calculation method see page 372



Bio-based content

(6109262, 6109263, 6109264, 6109265):
Frame consists of 45% bio-based plastic
(biogenic origin: castor oil plant), certified
in accordance with EN ISO 16321

Prescription safety spectacles

uvex RX bc metal frames

Basic collection
uvex RX bc metal

classic
timeless
virtually unrestricted prescription lenses



6109105



6109112

uvex RX bc 5103

- classic design metal frame with double bridge
- transparent side shields
- anatomically adjustable, soft nose pads and easily adjustable earpieces deliver exceptional fit

uvex RX bc 5103	
Art. no.	6109105
Ref. no.	5103 1400 55/17
Lens diameter	55 mm
Bridge width	17 mm
Colour	gunmetal, matt
Marking on frame	W 166 FT CE

uvex RX bc 5108

- slim, expressive metal frame
- transparent side shields
- very good fit with anatomically adjustable nose bridge and easily adjustable earpieces

uvex RX bc 5108	
Art. no.	6109112
Ref. no.	5108 3400 54/19
Lens diameter	54 mm
Bridge width	19 mm
Colour	steel blue
Marking on frame	W 166 FT CE

previously: uvex 9155 mercury



6109114



6109115

uvex RX bc 5109

- modern, rounded metal frame
- transparent side shields
- anatomically adjustable nose pads and ear-pieces ensure an exceptional fit

uvex RX bc 5109	
Art. no.	6109114
Ref. no.	5109 6100 50/19
Lens diameter	50 mm
Bridge width	19 mm
Colour	gold
Marking on frame	W 166 FT CE

uvex RX bc 5110

- classic, square metal frame
- transparent side shields
- anatomically adjustable nose pads and ear-pieces ensure an exceptional fit


uvex RX bc 5110	
Art. no.	6109115
Ref. no.	5110 1300 55/17
Lens diameter	55 mm
Bridge width	17 mm
Colour	anthracite
Marking on frame	W 166 FT CE

Prescription safety spectacles

uvex RX cb

custom bridge
uvex RX cb

perfect fit for
high cheekbones
wide temples
flat nose bridge



6109232

uvex RX cb 5580

- wide fitting plastic frame for the best fit
- frame design with side shields and integrated brow guard
- easily adjustable, soft-form ear pieces for extra comfort
- ideal for individuals with a flat nose bridge, high cheekbones and/or wide temples.
- tested for use with Asian headform 2M, DIS ISO 18526-4:2018

uvex RX cb 5580

Art. no.	6109232
Ref. no.	5580 3015 57/14
Lens diameter	57 mm
Bridge width	14 mm
Colour	drk blue, grey
Marking on frame	W 166 FT CE



6109233

uvex RX cb 5581











- plastic frame with extra wide temple width
- frame design with side shields and integrated brow guard
- easily adjustable, soft-form ear pieces for extra comfort
- ideal for individuals with a flat nose bridge, high cheekbones and/or wide temples.
- tested for use with Asian headform 2M, DIS ISO 18526-4:2018

uvex RX cb 5581

Art. no.	6109233
Ref. no.	5581 1542 58/14
Lens diameter	58 mm
Bridge width	14 mm
Colour	drk red, grey
Marking on frame	W 166 FT CE

Prescription safety spectacles

Lens options uvex RX bc for plastic and metal frames · uvex RX cb

Focus type		Lens type	Parameter for centering of the lenses
Description			Specific height Box measure
Single vision			
<ul style="list-style-type: none"> - Correction of visual defect in far, in-between or near distance 		Single vision, Single vision HD	Single vision HD ≥ centre of lens
Certified prescription range			
Comfort lenses			
<p>Nahcomfort</p> <ul style="list-style-type: none"> - Version with expanded near vision - Ideal for workplace environments of 30 cm to approx. 2 m 		Nahcomfort Standard, Nahcomfort Optima Versions see page 28	min. 17 mm
<p>Distanzcomfort</p> <ul style="list-style-type: none"> - Calculation of the individual correction for defined distances (1 m, 2 m or 4 m) 		Distanzcomfort Optima	min. 17 mm
<p>Single vision Relax</p> <ul style="list-style-type: none"> - To accommodate the prescription for the lower part of the lens, the prescription is increased by +0.5 of a diopter 		Single vision Relax	min. 17 mm
Certified prescription range			
Bifocals			
<ul style="list-style-type: none"> - Correction of visual defect in far and reading distance - Visible segment for near distance - Steplike change from far distance to near distance at the edge of segment - Instantly well-tolerated, visible edge of segment supports orientation 		Width of segment: 28 mm, curved	
Certified prescription range			
Varifocals			
<ul style="list-style-type: none"> - Correction of visual defect in far, in-between and near distance - Gliding change from far distance to near distance (progressive canal) - The non-visible gliding zone corrects in-between distances 		Varifocal Standard - Standard area for far distance and near distance - Long, narrow canal of progression	min. 23 mm
		Varifocal Pro Work - Large area for far distance - Wide canal of progression - Optimized area for reading distance	min. 20 mm
		Varifocal Piccolo - Suitable for flat frames - Large area for far distance and near distance - Shortened canal of progression	min. 17 mm
		Varifocal Top One - Very comfortable, large long-distance and close-up field of vision - Wide canal of progression for added convenience - Minimal blur in peripheral vision	min. 19 mm
		Varifocal Optima, Varifocal Optima HD - Individual adjusted multifocal lens of latest generation - Wide field of view for any distance - Improved design - Almost no blurred zones in periphery area >> Version HD see page 28	Optima min. 17 mm Optima HD min. 16 mm (depending on the corridor length)
Certified prescription range			

► The overview shows the maximum prescription range which is approved and certified.
Depending on the size of the frame and the lens material, further restrictions may apply.

Material							Extras, optional					
CR 39	HI 1.6	Plastic HI 1.67	PC	Trivex	Silicate Hard glass	Normal AR	Multi AR	Super AR	UV blue protect	Tint	Variomatic brown	
■	■	■	■	■	HD not available	■	■	■	■	■	■	
	incl. hard coating recommended from +/- 4.0 dpt.	incl. hard coating only available with SAR recommended from +/- 6.0 dpt.	incl. hard coating	incl. hard coating only available with SAR		only single vision	only single vision, not for hard glass	■	only HI 1.67 or PC		only Polycarbonate or Trivex	
+10.0 to -10.0 dpt. at maximum value cyl. ± 8.0 dpt.	+12.0 to -13.0 dpt. at maximum value cyl. ± 8.0 dpt.	+13.0 to -14.5 dpt. at maximum value cyl. ± 8.0 dpt.	+9.5 to -12.0 dpt. at maximum value cyl. ± 8.0 dpt.	+8.0 to -11.0 dpt. at maximum value cyl. ± 7.0 dpt.	+7.0 to -6.0 dpt. at maximum value cyl. ± 4.0 dpt.						+7.5 to -8.5 dpt. at maximum value cyl. ± 6.0 dpt.	
Standard/ Optima	only Optima	only Optima	Standard/ Optima	only Optima	—	■	not for hard glass	■	only HI 1.67 or PC	—	—	
■	■	■	■	■	—	■	not for hard glass	■	only HI 1.67 or PC	—	—	
■	■	■	■	■	—	■	not for hard glass	■	only HI 1.67 or PC	—	—	
+9.0 to -7.5 dpt. at maximum value cyl. ± 6.0 dpt.	+8.0 to -8.0 dpt. at maximum value cyl. ± 6.0 dpt.	+9.0 to -10.0 dpt. at maximum value cyl. ± 6.0 dpt.	+9.0 to -4.5 dpt. at maximum value cyl. ± 6.0 dpt.	+7.0 to -6.0 dpt. at maximum value cyl. ± 4.0 dpt.	+6.0 to -4.5 dpt. at maximum value cyl. ± 4.0 dpt.							
■	■	—	■	—	■	■	not for hard glass	■	—	■	—	
+7.0 to -8.0 dpt. at maximum value cyl. ± 6.0 dpt. Add. +3.0	+8.5 to -10.5 dpt. at maximum value cyl. ± 8.0 dpt. Add. +3.0		+10.0 to -10.0 dpt. at maximum value cyl. ± 6.0 dpt. Add. +3.0		+6.0 to -6.0 dpt. at maximum value cyl. ± 4.0 dpt. Add. +3.0							
■	■	■	■	—	■	■	not for hard glass	■	—	■	only Polycarbonate	
■	■	■	■	■	■	■	not for hard glass	■	only HI 1.67 or PC	■	only Polycarbonate or Trivex	
■	■	■	■	—	■	■	—	■	—	■	only Polycarbonate	
■	■	■	■	—	■	■	not for hard glass	■	only HI 1.67 or PC	■	only Polycarbonate	
■	■	■	■	■	—	only Optima	only Optima not for hard glass	■	only HI 1.67 or PC	■	only Polycarbonate or Trivex	
+6.0 to -10.0 dpt. at maximum value cyl. ± 6.0 dpt. Add. +3.0	+9.5 to -12.0 dpt. at maximum value cyl. ± 6.0 dpt. Add. +3.0	+10.0 to -12.0 dpt. at maximum value cyl. ± 6.0 dpt. Add. +3.0	+9.5 to -10.0 dpt. at maximum value cyl. ± 6.0 dpt. Add. +3.0	+6.0 to -13.0 dpt. at maximum value cyl. ± 6.0 dpt. Add. +3.0	+6.0 to -6.0 dpt. at maximum value cyl. ± 4.0 dpt. Add. +3.0						+7.5 to -10.0 dpt. at maximum value cyl. ± 6.0 dpt. Add. +3.0	

uvex

Prescription safety spectacles

uvex RX cd

comfort and design

uvex RX cd

modern

sporty

protective functions integrated into
frame design



Reflective uvex logo



6109257





6109249

uvex RX cd 5521 planet • uvex RX cd 5521

- stylish plastic frame with reflective uvex logo
- transparent lens frame for an unrestricted field of view
- good fit thanks to anatomically shaped nose bridge
- sporty arms made from a combination of soft and hard components to ensure increased comfort and non-slip fit


Art. no.	uvex RX cd 5521 planet 6109257	uvex RX cd 5521 6109249
Ref. no.	5521 1369 54/22	5521 1813 54/22
Lens diameter	54 mm	54 mm
Bridge width	22 mm	22 mm
Colour	anthracite, jade	silver, anthracite
Marking on frame	W 166 F CE	W 166 F CE

 CO2 footprint:
0.61 kg CO₂ e 05/2023 (6109257),

 Bio-based content (6109257): hard components of the frame consist of 38% bio-based plastic (biogenic origin: castor oil plant), certified in accordance with EN ISO 16321

Prescription safety spectacles

uvex RX cd



uvex RX cd 5518 successor model



uvex RX cd 5520 successor model

uvex RX cd 5525

- plastic frame in a sporty design
- transparent lens carrier for an unrestricted field of vision
- good fit thanks to anatomically shaped nose area
- ear-pieces with hard and soft components ensure a non-slip fit
- completely metal-free



uvex RX cd 5525		
Art. no.	6109258	6109259
Ref. no.	5525 1015 53/22	5525 1030 53/22
Lens diameter	53 mm	53 mm
Bridge width	22 mm	22 mm
Colour	black, grey	black, dark blue
Marking on frame	16321 W U1.2 G0 C 1-M CE	16321 W U1.2 G0 C 1-M CE

uvex RX cd 5526

- plastic frame in a sporty design
- translucent lens carrier for an unrestricted field of vision
- good fit thanks to anatomically shaped nose area
- soft, easily adjustable ear-pieces with metal core



uvex RX cd 5526		
Art. no.	6109260	6109261
Ref. no.	5526 1015 54/18	5526 1341 54/18
Lens diameter	54 mm	54 mm
Bridge width	18 mm	18 mm
Colour	black, grey	anthracite, red
Marking on frame	W 166 F CE	W 166 F CE

CO₂ footprint: 0.53 CO₂ e kg 07/2025 (6109258, 6109259), calculation method see page 372

Bio-based content (6109258, 6109259): hard components of the frame consist of 38% bio-based plastic (biogenic origin: castor oil plant), certified in accordance with EN ISO 16321

▶ Please note the glazing options for uvex RX cd on pages 398/399.

Prescription safety spectacles

uvex RX cd



6109254




6109255




uvex RX cd 5524 planet

- modern, close-fitting plastic frame
- translucent frame colour for an unobstructed field of vision
- frame design with integrated side shields and upper eye coverage
- soft, adjustable nose bridge
- easily adjustable soft-form comfort ear-pieces

uvex RX cd 5524 planet		
Art. no.	6109254	6109255
Ref. no.	5524 2513 53/16	5524 2513 57/16
Lens diameter	53 mm	57 mm
Bridge width	16 mm	16 mm
Colour	translucent, anthracite	translucent, anthracite
Marking on frame	W 166 F CE	W 166 F CE

 CO2 footprint:
0.71 kg CO₂ e 05/2023 (6109254),
0.74 kg CO₂ e 05/2023 (6109255)

 Bio-based content (6109254, 6109255): hard components of the frame consist of 38% bio-based plastic (biogenic origin: castor oil plant), certified in accordance with EN ISO 16321



6109225



6109226

uvex RX cd 5514

- close-fitting plastic frame
- transparent side shields and integrated brow guard frame design
- soft, adjustable nose bridge
- easily adjustable soft-form comfort ear pieces

uvex RX cd 5514		
Art. no.	6109225	6109226
Ref. no.	5514 1033 53/18	5514 1045 55/18
Lens diameter	53 mm	55 mm
Bridge width	18 mm	18 mm
Colour	black, blue	black, red
Marking on frame	W 166 F CE	W 166 F CE

► Please note the glazing options for uvex RX cd on page 22/23

Prescription safety spectacles

uvex RX cd 5528 · uvex RX cd 5528 tight-fit-kit



individually adjustable



universal

6109266



uvex RX cd 5528

- plastic frame in a sporty design with stylish colour gradient
- translucent side protection for an unrestricted field of vision
- air vents at the top help maintain comfort in the eye area
- soft, adjustable nose bridge
- sporty side arms made from a combination of soft and hard components to ensure increased comfort and non-slip fit
- soft, adjustable ear-pieces with metal core



large lens height



subtle colour gradient



non-slip, pressure-free fit




unrestricted field of vision

uvex RX cd 5528		
Art. no.	6109266	6109267
Ref. no.	5528 1091 56/18	5528 1091 59/18
Lens diameter	56 mm	59 mm
Bridge width	18 mm	18 mm
Colour	translucent, black	translucent, black
Marking on frame	16321 W U2,5 G2 C 1-M CE	16321 W U2,5 G2 1-M/1-L CE
Compatible with	6118018	6118019

CO₂ footprint: 0.43 kg CO₂e 07/2025 (6109266, 6109267), calculation method see page 372

Bio-based content (6109266, 6109267): Hard components of the frame consist of 31% bio-based plastic (biogenic origin: castor oil plant), certified in accordance with EN ISO 16321



Headband
Fitted quickly – for a firm, secure fit



uvex RX cd 5528 with uvex RX cd 5528 tight-fit-kit
6109266 + 6118018



Seal
Simply clip into the air vents of the frame



Accessories for an enhanced tight fit

uvex RX cd 5528 tight-fit-kit

- set consisting of seal and headband
- seal made of hard and soft components for a tight fit
- headband for a more secure fit, can be fitted straight onto the side arms

uvex RX cd 5528 tight-fit-kit		
Art. no.	6118018	6118019
Colour	black	black
Marking on frame	16321 W C CE	16321 W C CE
Compatible with	6109266	6109267
Order unit	PC	PC


► Please note the glazing options for uvex RX cd on pages 398/399.

Prescription safety spectacles

uvex RX cd 5522

uvex RX cd 5522 tight-fit-kit

FLEXIBLE / ROBUST / SAFE



uvex RX cd 5522

- modern plastic frame in a robust design
- translucent frame colour for an unobstructed field of vision
- air vents at the top and side
- soft, adjustable nose bridge
- sporty arms made from a combination of soft and hard components to ensure increased comfort and non-slip fit
- soft, adjustable ear-pieces with metal core




Headband
› easy fitting – for a more secure fit

Accessories for extra protection against liquids

uvex RX cd 5522 tight-fit-kit

- set consisting of seal and headband
- seal made of hard and soft components provides a tight fit
- protection against liquids (droplets) – marking 3, in accordance with EN 166
- headband for a more secure fit, can be fitted straight onto the side arms



Seal
› simply clip into the upper and side air vents of the frame to close them and fix the seal

6118012



	uvex RX cd 5522	uvex RX cd 5522 tight-fit-kit
Art. no.	6109250	6118012
Ref. no.	5522 2533 58/15	
Lens diameter	58 mm	
Bridge width	15 mm	
Colour	translucent-grey, blue	black, anthracite
Marking on frame	Frame: W 166 F CE	Face seal: W 166 3F CE
Compatible with	6118012	6109250
Order unit		PC

uvex RX cd 5522 (6109250) with uvex RX cd 5522 tight-fit-kit (6118012)

► Please note the glazing options for uvex RX cd on pages 398/399.

Prescription safety spectacles

uvex RX cd



6109236

uvex RX cd 5520

- contemporary plastic frame in stylish colours
- good fit thanks to anatomically shaped nose bridge
- translucent lens frame for an unobstructed field of view
- uvex Comfort Sliders allow the side arm length and inclination to be adjusted for a customised fit
- the spectacles can also be worn without uvex Comfort Sliders
- completely metal-free

uvex RX cd 5520	
Art. no.	6109236
Ref. no.	5520 1344 54/18
Lens diameter	54 mm
Bridge width	18 mm
Colour	anthracite, blue
Marking on frame	W 166 F CE

► Please note the glazing options for uvex RX cd on page 22/23

* Frame to be discontinued, available while stocks last



5505 seal 55/19
5505 seal 57/19



6118000 with 5505 seal 57/19



6118001 with 5505 seal 55/19

uvex RX cd 5505 seal

- foam seal frame for uvex RX cd 5505 for use when working with dust, chips or fluids
- complies with EN 166 "Protection against liquid droplets and splashes" (category "3")

uvex RX cd 5505 seal		
Art. no.	6118000	6118001
Ref. no.	5505 seal 55/19	5505 seal 57/19
Lens diameter	55 mm	57 mm
Bridge width	19 mm	19 mm
Colour	black	black
Compatible with	Art. no. 6108208	Art. no. 6108209
	Art. no. 6109208	Art. no. 6109209
	Art. no. 6109214	Art. no. 6109215
Seal marking	W 166 3 F CE	W 166 3 F CE



6109218
6109235

uvex RX cd 5505 flip-up welding protection

- flip-up with welding protection lenses, non-prescription
- level of protection 5 (welding), suitable for autogenous welding
- new filter technology with grey-tinted lenses provides reliable protection against UV and infrared radiation as well as ensuring perfect colour recognition
- Note: welding protection lenses do not provide sufficient protection against laser beams!
- level of protection 5 in accordance with EN 169 (welding), mech. strength F in accordance with EN 166

uvex RX cd 5505 flip-up welding protection		
Art. no.	6109218	6109235
Ref. no.	5505 9905 55/19	5505 9905 57/19
Lens diameter	55 mm	57 mm
Bridge width	19 mm	19 mm
Colour	black, green	black, green
Features: flip-up		
Lens	PC grey, welding protection 5 uvex infradur plus	PC grey, welding protection 5 uvex infradur plus
Lens marking	5 W1 FTK CE	5 W1 FTK CE
Marking on frame	W 166 F CE	W 166 F CE

* Frame to be discontinued, available while stocks last

SBU Occupational Health

Individual personal protective equipment from uvex

**ONE BRAND.
ONE VISION.
ONE MISSION.**



OUR MISSION

#protecting people

The uvex brand mission. This is our objective and our responsibility. uvex protects people – when working, playing sport and pursuing leisure activities.

Decades of experience enable us to transfer expertise continuously between the sectors of industrial safety and top-level sport, and provides the foundation on which we are able to continuously develop our products.

It allows us to create innovations and solutions based on advanced technologies that reliably protect people – whether they are on a production line, on the ski slopes or on a mountain bike.

OUR FUTURE

Sustainable actions and social responsibility

If you rely on uvex, you are guaranteed sustainable actions. From environmental protection to social commitment: uvex puts corporate responsibility at the forefront of its daily business.

The focus of our commitment is to protect people:

- sustainable product concept
- avoidance of the use of hazardous beyond the requirements of the REACH regulation (the uvex banned hazardous substances list)
- uvex social standard for all manufacturing plants
- social commitment (e.g. Rainer Winter Foundation, Vision for the World)

OUR SERVICE

Time and location adapted to your needs

As an experienced specialist in occupational safety, uvex is able to offer an all-round professional service for individual personal protective equipment and meet the specific requirements of your company. Individual PPE products demand a wealth of expertise in the

consultation stage. This is why the adaptation is made by highly qualified experts – such as opticians, audiologists or orthopaedic shoe manufacturers – at a time and location to suit your needs.

Digital service tools

uvex centRX · uvex RX OMS · uvex RX lens consulting

Maximum service with maximum flexibility

With our uvex RX OMS, uvex RX lens consulting and uvex centRX digital service tools, we offer useful service tools in the fields of prescription safety spectacles and prescription VDU spectacles, which provide you with valuable information at a glance to facilitate your daily work or the ordering process.



uvex centRX – customisation – simple, fast, digital

The uvex centRX [pronounced ‘sentriks’] photo-centring tool is a web-based, easy-to-use solution for quickly and reliably determining the necessary centring parameters for ordering uvex safety and VDU prescription spectacles.

It offers customers, retailers and service partners the opportunity to determine the necessary parameters via a photo and to order glasses digitally using the simple menu navigation. The centring requirements of individual focus groups are stored in the application, so that the possibility of calculation errors in determining the specific height is eliminated.

Your benefits:

Spectacles configuration

- ✓ Easy and online
 - ✓ Based on individualised customer product ranges
 - ✓ Immediate feedback on feasibility according to EU type certification
 - ✓ Organized data management for your configuration orders incl. status tracking
- ✓ Simple registration
- ✓ Create multiple user logins for one account
- ✓ Available in several languages

What you need for uvex RX OMS:

- ✓ PC or laptop with Edge or Chrome browser
- ✓ Internet connection

uvex RX lens consulting – Optimal selection of products – conveniently online

What are the advantages of the different lens types and coatings for innovative uvex prescription safety spectacles?

Find the optimum product to meet requirements quickly and easily using the practical uvex RX app.



Prescription safety spectacles

Lens options for uvex RX cd














uvex RX cd 5521



uvex RX cd 5505



uvex RX cd 5505 flip-up

					Lens type	Parameter for centering of the lenses	
Description						Specific height	Box measure
Single vision							
					Single vision, Single vision HD	Single vision HD	min. centre of lens
Prescription range							
Comfort lenses							
					Nahcomfort Standard, Nahcomfort Optima Versions see page 28	min. 17 mm	
Nahcomfort Standard	Nahcomfort Optima	Distanzcomfort Optima	Single vision Relax		Distanzcomfort Optima	min. 17 mm	
					Single vision Relax	min. 17 mm	
Prescription range							
Bifocals							
					Width of segment: 28 mm, curved		
Prescription range							
Varifocals							
					Varifocal Standard	min. 23 mm	
Varifocal Standard	Varifocal Pro Work	Varifocal Piccolo	Varifocal Top One	Varifocal Optima	Varifocal Pro Work	min. 20 mm	
					Varifocal Piccolo	min. 17 mm	
					Varifocal Top One	min. 19 mm	
					Varifocal Optima	min. 17 mm	
					Varifocal Optima HD	min. 16 mm (depending on the corridor length)	
Prescription range							

► In order to ensure optimum vision, uvex compensate the values in accordance to the frame wrap angle (FWA).
 The overview below provides information on the lens options for uvex RX cd frames.
 Please also ensure the frame fits correctly.



uvex RX cd 5514



uvex RX cd 522

	Material					Extras, optional					
	Plastic					Normal AR	Multi AR	Super AR	UV blue protect	Tinting	Variomatic brown
CR 39	HI 1.6	HI 1.67	PC	Trivex							
■	■	■	■	■	■	■	■	■	■	■	■
		incl. hard coating	incl. hard coating only available with SAR	incl. hard coating	incl. hard coating only available with SAR	only single vision	only single vision		only HI 1.67 or PC		only Polycarbonate or Trivex
+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.						+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.
Standard/Optima	only Optima	only Optima	Standard/Optima	only Optima	■	■	■	only Optima, HI 1.67 or PC	–	–	
■	■	■	■	■	■	■	■	only HI 1.67 or PC	–	–	
■	■	■	■	■	■	■	■	only HI 1.67 or PC	–	–	
+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.						
■	■	–	■	–	■	■	■	–	■	–	
+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.		+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.								
■	■	■	■	–	■	■	■	–	■	–	only Polycarbonate
■	■	■	■	■	■	■	■	only, HI 1.67 or PC	■	–	only Polycarbonate or Trivex
■	■	■	■	–	■	–	■	–	■	–	only Polycarbonate
■	■	■	■	–	■	■	■	only, HI 1.67 or PC	■	–	only Polycarbonate
■	■	■	■	■	■	■	■	only, HI 1.67 or PC	■	–	only Polycarbonate or Trivex
■	■	■	■	■	■	only Optima	only Optima	■	only, HI 1.67 or PC	■	only Polycarbonate or Trivex
+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.	+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.						+6.0 to -6.0 dpt. at maximum value cyl. ±4.0 dpt.

Prescription safety spectacles

uvex RX sp



sporty
uvex RX sp

dynamic
wrap-around design
protective functions integrated in
frame design



uvex anatomic sport lens

- we only use lenses with a base curve that is identical to the curvature of the frame.
- prescription values are recalculated based on the angle of the lenses and taken into account during the glazing process..



uvex RX sp 5510

- sporty, plastic “wraparound” design with curved lenses and anatomic sport glazing
- side shield and integrated brow guard frame design
- good fit with anatomically shaped soft nose bridge
- sporty arms with a combination of soft and hard components ensure increased comfort and non-slip fit

uvex RX sp 5510		
Art. no.	6109216	6109217
Ref. no.	5510 1217 62/17	5510 1248 62/17
Lens diameter	62 mm	62 mm
Bridge width	17 mm	17 mm
Colour	matt black, light grey	matt black, orange

► Please note the glazing options for uvex RX sp on pages 28/29

Prescription safety spectacles

uvex RX sp



6109221

uvex RX sp 5512

- sporty, plastic “wraparound” design with curved lenses and anatomic sport glazing
- uvex tight-fit-kit consisting of headband and foam material available
- side shield and integrated brow guard frame design
- the arms can be replaced with a headband for a more secure fit when working in extreme conditions
- the foam material guarantees a close and firm fit.
- very good fit with anatomically adjustable, soft nose bridge
- sporty side arms with a combination of soft and hard components ensure increased comfort and non-slip fit

Applications in combination with the tight-fit-kit:

- working in extreme situations, such as overhead or in confined spaces
- working with fluids (drops) or chips and dust



6118005



6109221 assembled with uvex tight-fit-kit 6118005

uvex RX sp 5512	
Art. no.	6109221
Ref. no.	5512 1348 65/16
Lens diameter	65 mm
Bridge width	16 mm
Colour	anthracite, orange
Marking on framer	W 166 F CE

uvex tight-fit-kit	
Art. no.	6118005
Design	uvex tight-fit-kit for uvex RX sp 5512
Colour	anthracite, orange
Tight-fit-kit marking	W 166 3 F CE

► Please note the glazing options for uvex RX sp on page 24/25

* Frame to be discontinued, available while stocks last



6109222

uvex RX sp 5513

- sporty, plastic “wraparound” design with large lenses and anatomic sport glazing
- side shield and integrated brow guard frame design
- good fit due to anatomically shaped soft nose bridge
- sporty arms with a combination of soft and hard components ensure increased comfort and non-slip fit

uvex RX sp 5513	
Art. no.	6109222
Ref. no.	5513 1577 62/16
Lens diameter	62 mm
Bridge width	16 mm
Colour	grey, light green
Marking on frame	W 166 F CE

► Please note the glazing options for uvex RX sp on pages 24/25

* Frame to be discontinued, available while stocks last

uvex

uvex RX cf 9501

goggle with direct prescription lenses

close fit
uvex RX cf

close-fitting
all-round protection
direct glazing
solutions using RX insert

uvex RX cf 9501

- goggles with custom prescription
- direct prescription lenses provide exceptional optical quality without aberrations or loss of light
- comfortable TPE frame, stays comfy even when worn for longer periods
- high level of mechanical strength ("B", 120 m/s)
- meets the requirements for additional markings 3 (liquids, droplets) and 4 (coarse dust)

uvex RX goggle 9501	
Art. no.	6109501
Ref. no.	9501 1333 61/14
Lens diameter	61 mm
Bridge width	14 mm
Colour	anthracite, blue
Marking on frame	W 166 34 B CE

► Please note the glazing options for uvex RX sp on pages 20/21



Direct prescription lenses
Prescription safety lenses are inserted directly into the goggle frame according to the individual prescription strength



Sophisticated ventilation
Direct and indirect air vents ensure optimum protection and excellent ventilation for "eye zone" comfort.



Flexible headband clip
The flexible headband clip allows the goggle to adjust to different facial shapes for a customised fit. The comfortable fabric headband keeps the uvex RX cf 9501 securely in place.

Prescription safety spectacles

uvex RX cf



6108200

uvex RX cf 5500

- spectacles with all-round protection
- fixed RX insert for your individual prescription
- meets the requirements for additional markings 3 (liquids, droplets) and 4 (coarse dust)
- perfect fit providing reliable protection: The side arms can be adjusted to a variety of different lengths, allowing the glasses to be adapted to suit all facial shapes
- flexible soft components adapt to the wearer's face contours

uvex skyguard NT RX 5500	
Art. no.	6108200
RX insert lens diameter	48mm
RX insert bridge width	20mm
Colour	blue, grey
Marking on frame	W 166 34F CE
Lenses	PC clear
Lens marking	2C-1,2W 1 FKN

► Please note the glazing options for uvex RX cd on pages 20/21



6108201

uvex RX cf 5501

- small goggles with fixed RX insert to suit your individual prescription
- meets the requirements for additional markings 3 (liquids, droplets) and 4 (coarse dust)
- highly compatible with other PPE
- low-volume frame design
- indirect ventilation

uvex carbonvision RX 5501	
Art. no.	6108201
RX insert lens diameter	48 mm
RX insert bridge width	20 mm
Colours	black, grey
Marking on frame	W 166 34 B CE
Lens	PC clear
Lens Marking	2C-1,2 W 1 FKN

► Please note the glazing options for uvex RX sp on pages 20/21



9308145

uvex u-sonic with RX insert

The compact design means the u-sonic model is not suitable for wearing over prescription glasses as cover specs. However, the uvex u-sonic can be combined with prescription lens inserts as an RX version. This ensures optimal protection for those requiring prescription glasses.

uvex u-sonic	
Art. no.	9308145
Version	uvex supravision excellence
Standard	EN 166, EN 170
Lens	PC clear, 2C-1.2 W1BKN CE
Colour	anthracite, lime


















6118106



9308145 assembled with uvex RX insert

Prescription safety spectacles

Lens options for uvex RX sp models · Special lenses for uvex RX cf 9501

uvex RX sp 5519, uvex RX sp 5510		Important note	Lens type	Parameter for centering of the lenses
Description				Specific height Box measure
	Single vision	for uvex RX sp 5510: Minimum PD ≥ 32.0 mm Fitting height ≥ centre of lens	Single vision Single vision HD	
	Comfort lenses			
	   Nahcomfort Optima Distanzcomfort Optima Single vision Relax	for uvex RX sp 5510: Minimum PD ≥ 32.0 mm Fitting height ≥ centre of lens	Nahcomfort Optima Distanzcomfort Optima Single vision Relax	min. 17 mm min. 17 mm min. 17 mm
	Varifocals	for uvex RX sp 5510: Minimum PD ≥ 32.0 mm Fitting height ≥ centre of lens		
	  Varifocal Pro Work Varifocal Optima Varifocal Optima HD		Varifocal Pro Work Varifocal Optima Varifocal Optima HD	min. 20 mm min. 17 mm min. 16 mm
	Prescription range			
uvex RX sp 5512, uvex RX sp 5513		Important note	Lens type	Parameter for centering of the lenses
Description				Specific height Box measure
	Single vision	Minimum PD ≥ 32.0 mm Fitting height ≥ centre of lens	Single vision Single vision HD	
	Comfort lenses			
	   Nahcomfort Optima Distanzcomfort Optima Single vision Relax	Minimum PD ≥ 32.0 mm Fitting height ≥ centre of lens	Nahcomfort Optima Distanzcomfort Optima Single vision Relax	min. 17 mm min. 17 mm min. 17 mm
	Varifocals	Minimum PD ≥ 32.0 mm Fitting height ≥ centre of lens		
	  Varifocal Pro Work Varifocal Optima Varifocal Optima HD		Varifocal Pro Work Varifocal Optima Varifocal Optima HD	min. 20 mm min. 17 mm min. 16 mm
	Prescription range			
uvex RX goggle		Important note	Lens type	Parameter for centering of the lenses
Description				Specific height Box measure
	Single vision	When using PC Minimum PD ≥ 32.0 mm When using Trivex Minimum PD ≥ 34.0 mm	Single vision Single vision HD	
	Varifocals			
	  Varifocal Pro Work Varifocal Optima Varifocal Optima HD	When using PC Minimum PD ≥ 32.0 mm When using Trivex Minimum PD ≥ 34.0 mm	Varifocal Pro Work Varifocal Optima Varifocal Optima HD	min. 20 mm min. 17 mm min. 16 mm
	Prescription range			

► In order to ensure optimum vision, uvex only uses the special uvex anatomic sport glazing.
 The overview below provides information on the lens options for uvex RX sp frames and uvex RX goggle.
 Please also ensure the frame fits correctly.

Material					Extras, optional					
CR 39	HI 16	Plastic HI 1.67	PC	Trivex	Normal AR	Multi AR	Super AR	UV blue protect	Tint	Variomatic brown
■	■	■	■	■	■	■	■	■	■	■
	incl. hard coating	incl. hard coating only available with SAR	incl. hard coating	incl. hard coating				only HI 1.67 or PC		only Polycarbonate or Trivex
■	■	■	■	–	■	■	■	only HI 1.67 or PC	–	–
■	■	■	■	–	■	■	■	only HI 1.67 or PC	–	–
■	■	■	■	–	■	■	■	only HI 1.67 or PC	–	–
■	■	■	■	■	■	■	■	only HI 1.67 or PC	■	only Polycarbonate or Trivex
■	■	■	■	■	■	■	■	only HI 1.67 or PC	■	only Polycarbonate or Trivex
■	■	■	■	■	■	■	■	only HI 1.67 or PC	■	only Polycarbonate or Trivex
+ 5.0 to – 5.0 dpt. at maximum value cyl. ±2.0 dpt.	+ 5.0 to – 5.0 dpt. at maximum value cyl. ±2.0 dpt.	+ 5.0 to – 5.0 dpt. at maximum value cyl. ±2.0 dpt.	+ 5.0 to – 5.0 dpt. at maximum value cyl. ±2.0 dpt.	+ 5.0 to – 5.0 dpt. at maximum value cyl. ±2.0 dpt.						+ 5.0 to – 5.0 dpt. at maximum value cyl. ±2.0 dpt.
■	■	■	■	■	■	■	■	■	■	■
	incl. hard coating	incl. hard coating only available with SAR	incl. hard coating	incl. hard coating				only HI 1.67 or PC		only Polycarbonate or Trivex
■	■	■	■	–	■	■	■	only HI 1.67 or PC	–	–
■	■	■	■	–	■	■	■	only HI 1.67 or PC	–	–
■	■	■	■	–	■	■	■	only HI 1.67 or PC	–	–
■	■	■	■	■	■	■	■	only HI 1.67 or PC	■	only Polycarbonate or Trivex
■	■	■	■	■	■	■	■	only HI 1.67 or PC	■	only Polycarbonate or Trivex
■	■	■	■	■	■	■	■	only HI 1.67 or PC	■	only Polycarbonate or Trivex
+ 3.5 to – 3.5 dpt. at maximum value cyl. ±2.0 dpt.	+ 3.5 to – 3.5 dpt. at maximum value cyl. ±2.0 dpt.	+ 3.5 to – 3.5 dpt. at maximum value cyl. ±2.0 dpt.	+ 3.5 to – 3.5 dpt. at maximum value cyl. ±2.0 dpt.	+ 3.5 to – 3.5 dpt. at maximum value cyl. ±2.0 dpt.						+ 3.5 to – 3.5 dpt. at maximum value cyl. ±2.0 dpt.
Material					Extras, optional					
CR 39	HI 16	HI 1.67	PC	Trivex	Normal AR	Multi AR	Super AR	UV blue protect	Tint	Variomatic brown
–	–	–	■	■	■	■	■	■	■	■
			incl. hard coating	incl. hard coating only available with SAR				only HI 1.67 or PC		only Polycarbonate or Trivex
–	–	–	■	■	■	■	■	only HI 1.67 or PC	■	only Polycarbonate or Trivex
–	–	–	■	■	■	■	■	only HI 1.67 or PC	■	only Polycarbonate or Trivex
–	–	–	■	■	■	■	■	only HI 1.67 or PC	■	only Polycarbonate or Trivex
			+ 3.5 to – 3.50 dpt. at maximum value cyl. ±2.0 dpt.	+ 3.5 to – 3.50 dpt. at maximum value cyl. ±2.0 dpt.						+ 3.5 to – 3.5 dpt. at maximum value cyl. ±2.0 dpt.


Prescription safety spectacles

Certification and marking

Certification


Individually manufactured uvex prescription safety spectacles are tested and certified by independent testing institutes at regular intervals according to the requirements of the current standard.

Marking

- frame and lenses are permanently marked
- if the markings on the lens and frame are different, the lower mechanical strength applies to the entire eye protection device
- according to the PPE regulation, uvex prescription safety spectacles must be marked with the factory symbol and production date:  MM/YYYY



Markings on lenses in accordance with EN 166



Mechanical strength

S	Increased strength
F	Low-energy impact (45 m/s or 162 km/h)
B	Medium-energy impact (120 m/s or 432 km/h)
T*	Tested under extreme temperatures (-5°C/+55°C)


Tinting levels

Marking	Light transmittance	Tint
1.2	74.4–100%	Clear
1.1 < 3.1		Self-tinting (variomatic)

Filter

2	UV protection filter (EN 170)
2C	UV protection filter with colour recognition (EN 170)
5	Sunglare filter for industrial use (EN 172)

Markings on frames in accordance in accordance with EN 166



Mechanical strength

S	Increased strength
F	Low-energy impact (45 m/s or 162 km/h)
B	Medium-energy impact (120 m/s or 432 km/h)
T*	Tested under extreme temperatures (-5°C/+55°C)

Additional markings*

None	General use
3	Protection against liquids (drops and splashes)
4	Protection against large dust particles with a grain size of > 5 µm

Prescription safety spectacles

New standard for safety eyewear EN ISO 16321

EN ISO 16321 – unpacking the new standard and what it means for your prescription safety spectacles

For more than 20 years, the EN 166 standard has defined all of the requirements and standards for safety eyewear within the European Union and the United Kingdom. EN 166 is now being replaced by EN ISO 16321. The new standard contains a range of international standards that will entail some significant changes to product requirements and test methods.

As a result, new certificates will be required for all prescription safety spectacles in accordance with EN ISO 16321.

The most important changes at a glance:

- EN ISO 16321 includes EN ISO 16321-1 (general requirements; UV, sunglare and IR filters), EN ISO 16321-2 (welding protection filters).
- New test heads and coverage areas have been defined, and certification of different head sizes (S, M, L) is now also permitted.
- The certification of all prescription safety spectacles (frames/lenses) will be updated.

Markings on lenses in accordance with EN ISO 16321

Mechanical strength


None	Drop ball test in accordance with EN ISO 16321 (basic requirement)
C	Low-energy impact (45 m/s or 162 km/h)
D	Medium-energy impact (80 m/s or 288 km/h)
T*	Tested under extreme temperatures (-5°C/+55°C)

Tinting levels

Marking	Light transmittance	Tints
UL1.2	74.4-100%	Clear
G1-3		Self-tinting (variomatic)

Filter

U	UV protection filter
UL	UV protection filter with colour recognition
G	Sunglare filter (variomatic)



Markings on frames in accordance with EN ISO 16321

Head sizes

1-S	Small, European test head
1-M	Medium, European test head (standard)
1-L	Large, European test head
2-S	Small, Asian test head
2-M	Medium, Asian test head
2-L	Large, Asian test head

Mechanical strength


None	Drop ball test in accordance with EN ISO 16321 (basic requirement)
C	Low-energy impact (45 m/s or 162 km/h)
D	Medium-energy impact (80 m/s or 288 km/h)
T*	Tested under extreme temperatures (-5°C/+55°C)

Additional markings*

3	Protection against liquids (drops and splashes)
4	Protection against large dust particles with a grain size of > 5 µm

Tinting levels

U1.2	Light transmittance 74.4-100%
-------------	-------------------------------



Filter

U	UV protection filter
----------	----------------------

* optional

Prescription safety spectacles

Focus types

Single vision lenses

Single vision

- defective vision caused by long-sightedness or short-sightedness is corrected

Single vision HD – the ultimate in customisation!

- free-form single-vision lens
- individual parameters such as cornea vertex distance, frame wrap angle and inclination are taken into account for production purposes.
- calculation of dioptres to an accuracy of one hundredth



Comfort lenses

- ideal for use at workstations with monitors
- comfort lenses relieve the eye when looking at objects close up and at intermediate distances thanks to their seamless correction areas
- comfort lenses are a good alternative if the prescription safety eyewear is only needed at workstations and distance vision (> 5 m distance) is not necessary.



Nahcomfort Standard, Nahcomfort Optima

- perfect solution for working distances between 30 cm and approx. 2 m
- the medium range of the lens surface is determined by the degression chosen and is designed for a distance of approx. 60 cm to 80 cm
- three versions are available, depending on the required reading addition (optional based on the age of the wearer)
- all that is needed to place an order are details of the close-range values and the required design (type A, B, C)
- when ordering the Nahcomfort Optima option, the inner surface of the raw lenses is calculated and manufactured, taking into account the correction, the glass curve and the distance between the eyes

Type A	Type B	Type C
Degression** 0.75 dpt	Degression** 1.25 dpt	Degression** 1.75 dpt
< 50 years	50 to 55 years	> 55 years

** Degression: Correction reduced, based on the close-range value!

Note:

Ideal for use in VDU spectacles. About 60% of degression is active at the centring cross, so the recommended adjustment applies on the main line of sight.

Distanzcomfort Optima

- perfect solution for working distances between 30 cm and around 1 m, 2 m or 4 m
- by specifying the viewing distance that is required at the workstation, the correction areas will be calculated individually
- all that is needed to place an order are details of the distance and close-range values (addition), the maximum viewing distance (one, two or four meters) as well as the centering parameters (pupillary distance and specific height)
- recommended adjustment: zero line of sight, distance values and addition

Single Vision Relax

- this type of lens is targeted at people over the age of 30
- an invisibly integrated change to the correction value of +0.5 dpt. in the lower area of the lens eases the strain on the eye when looking at near distances (accommodation support)
- the distance correction remains unchanged
- all that is needed to place an order the details of distance values and centring parameters (pupillary distance and specific height)
- we recommend Single Vision Relax lenses for professionals who use mobile devices (notebook, tablet, smartphone etc.) for their daily work

Prescription safety spectacles

Focus types



Bifocal lenses

Bifocal

- visibly ground segment for near vision ('reading field')
- instant wearer acceptance as visible edge helps eyes to adjust
- intermediate ranges are not corrected



Bifocal Comfort

- free-form bifocal lens with a rounded, blended near-vision area for a more aesthetic appearance
- instant wearer acceptance due to soft transition to the near-vision area
- handled in the same way as conventional bifocal lenses
- intermediate ranges are not corrected



Varifocal lenses

- gradual transition from distance to near vision, known as the progression zone
- the invisible progression zone also corrects intermediate distances
- clear vision at all viewing distances
- may require an initial adjustment phase

Varifocal Optima HD – the ultimate in customisation!

- free-form varifocal lens taking into account individual parameters such as cornea vertex distance, frame wrap angle and inclination
- calculation of dioptres to an accuracy of one hundredth



Varifocal OR

- free-form varifocal lens with a blended near-vision area in the upper section to make overhead work easier
- selection of the addition in the upper near-vision area (depending on the working distance)
- the addition in the upper near-vision segment depends on the addition in the progressive part of the lens
- the following can be selected:
 - type A: addition distribution: 100% bottom and 100% top
 - type B: addition distribution: 100% in the progressive near-vision area and 60% in the blended near-vision area
- type B example: addition: bottom 2.0 dpt. /top 1.2 dpt.

Prescription safety spectacles

Lens material



Polycarbonate

- mechanical strength 'F' (45 m/sec)
- organic material with very high breaking strength
- only partially chemical-resistant
- PC+ – polycarbonate with increased centre thickness and mechanical strength 'B' (120 m/sec), especially for the uvex RX goggle

Trivex™

- mechanical strength 'F' (45 m/sec)
- best all-round lens material
- excellent resistance to cleaning agents, oils and cosmetics and good scratch resistance
- lightweight, suitable for even higher prescription values

CR39, modified (plastic)

- mechanical strength 'S' (ball drop test)
- lightweight organic material suitable for chemicals and painting

UV blue protect

- good scratch resistance due to hard coating (optional)

A special absorber has been added to the lens material that completely filters out UV rays and reduces the blue light content.

- the lenses absorb UV radiation up to 400 nm at 100%, filter short-wave blue light until 410 nm almost completely and reduce the range from 410 nm to 420 nm around 86%.
- uvex UV blue protect lenses enhance contrast and effectively prevent signs of fatigue and age-related macular degeneration (AMD)
- UV blue protect is optionally available for polycarbonate (PC) lenses and HI 1.67

HI (high index)

Organic lenses with high refractive index – 1.6 or 1.67

- mechanical strength 'S' (ball drop test)
- organic material suitable for chemicals and painting
- the lens is thinner and more aesthetically pleasing


HI 1.6 recommended for a prescription > +/-4.0 dpt.
HI 1.67 recommended for a prescription > +/-6.0 dpt.

Hard glass, modified

(crown glass, silicate, mineral glass, glass)

- mechanical strength 'S' (ball drop test)
- highly scratch-resistant surface suitable for working with chemicals and paints
- heavy, not recommended for prescription values greater than +/-4.0 dpt.
- spark penetration when welding or grinding

- the mechanical strength of the lenses is guaranteed – clear lenses with UV blue protect are marked 2C-1.2 according to EN 170



Prescription safety spectacles

Finishes


Anti-reflective coating

Anti-reflective coating is applied to the inside and outside of lenses by means of vapour deposition. It significantly reduces reflections on the surfaces. It offers a cosmetic advantage and increases light transmission.

Three qualities are available:


- normal anti-reflective coating
- multiple anti-reflective coating
- super anti-reflective coating

Normal anti-reflective coating	Super anti-reflective coating
Good reflection reduction	Maximum reflection reduction
Metal oxide is applied once to each surface	Metal oxide is applied several times to each surface
Residual reflection \approx 4%	Residual reflection $<$ 2%



Scratch-resistant coating

To guarantee an ideal surface hardness, all our plastic lenses are given a hard coating (optional for CR 39).



Tint


Tinted lenses provide effective protection against glare in areas with high light intensity (for example, sunlight)

Constant tinting

- available in brown and grey
- tinting levels: 15%, 25%, 65%, 75%


Variable tinting – Variomatic™

- lenses tint automatically depending on the UV radiation and temperature
- tinting of between approx. 8% and 80%, in brown
- available as prescription safety spectacles in polycarbonate and Trivex™



Prescription safety spectacles

Special lenses



Special lenses for special requirements are available in combination with our RX cd 5505 flip-up models. The flip-up is fitted with non-prescription special lenses. The main frame is fitted with individual prescription safety lenses

Didymium

- special filter with high absorption at 589 nm, resulting in characteristic violet colour
- the 'bright yellow sodium flare' is filtered out
- lightweight polycarbonate filter with mechanical strength 'F' (45 m/s)
- level of protection 2-2 in accordance with EN 170
- marking: 2-2 W 1 F CE
- note: Didymium lenses do not provide increased protection against infrared radiation (IR)

Areas of application:

Glass production, glass processing, e.g. glass blowing

X-ray protection

- mineral lenses that provide protection against X-rays
- the lead equivalent of the protective lenses is 0.75
- the lead content in the lenses gives them their characteristic grey colour (approx. 10% colouring)
- marking: Pbeq 0.75
- note: Protective X-ray lenses are not tested and marked in accordance with EN 166

Areas of application:

e.g. crack and material testing

Welding protection

- welding protection level 5 in accordance with EN 169
- grey-tinted polycarbonate filters for reliable protection against UV and infrared radiation with mechanical strength 'F' (45 m/s)
- perfect colour perception during the welding process
- marking: 5 W 1 FTK CE
- note: Welding protection lenses do not provide sufficient protection against laser beams!

Areas of application:

Autogenous welding

CBR65

- contrast enhancement – For better contrast and comfortable vision, even in diffused light
- Blue light reduction – Blue light is reduced by up to 50% in extremely bright workplaces
- Relaxed vision – Reduced eye fatigue, even during longer periods of use
- 65% transmission – Slight tint for optimal protection against glare for high visual standards even in extremely bright, artificial light as well as natural light
- lightweight polycarbonate filter with mechanical strength 'F' (45 m/s)
- marking: 5-1.4 W 1 FK CE

Areas of application:

Workplaces with high visual standards in very bright artificial light or natural light

Polarisation filter

- polarising filters only let in radiation from one vibration direction – scattered radiation (e.g. reflection on the surface of water) is suppressed
- lightweight polycarbonate filter with mechanical strength 'F' (45 m/s)
- marking: 5-3.1 W 1 F CE

Areas of application:

- particularly suitable for workplaces with a high risk of glare and/or highly reflective surfaces
- offshore, maritime environment, construction industry

Benefit from our knowledge

The uvex academy provides qualified education and training in the fields of personal protective equipment (PPE) and health and safety at work.

All uvex academy training sessions are offered in-house or as company seminars. Seminars in accordance with your individual specifications can be developed on request.

- Protective eyewear
- Prescription safety spectacles/goggles
- Hearing protection
- Hand protection
- Head Protection
- Respiratory Protection
- Disposable Coveralls



The uvex academy is
your competent partner
for qualified training and further education.

You can find more information
at <https://www.uvex.co.za/en/learn-more/uvex-academy/about-us/>



uvex

DURBAN:

Tel: 031 569 6780

e-mail: info@uvex.co.za

PRETORIA

Tel: 012 345 6656

e-mail: safety@uvex.co.za

protecting people