## uvex







## uvex 2 GTX VIBRAM® · Shoe S3 WR HI HRO SRC · Lace-up boot S3 WR HI HRO SRC

General features:

- · lightweight and flexible, waterproof safety shoe / boot in S3 WR
- suitable for people allergic to chrome as made from synthetic materials
- · foamed polyurethane scuffcap helps increase product life of upper
- · elastic laces for quick, individual adjustment, normal laces also provided (shoe)

Protection features:

- 100% waterproof thanks to GORE-TEX® lining (WR label)
- · meets the ESD specification with leakage resistance less than 35 megaohms
- 100% metal-free uvex xenova® toe cap compact design, anatomical shape, good lateral stability, no thermal conductivity
- · ultra lightweight, double-layer sole made from optimal shock-absorbing polyurethane midsole and VIBRAM® rubber outsole with excellent anti-slip properties
- HI label for heat-insulating substructure (tested in accordance with standard at
- · HRO label for heat-resistant substructure for brief exposure up to +300°C
- secure grip when climbing on ladders due to the stabilising arch support
- penetration-resistant, non-metallic midsole in accordance with the latest safety standards, does not restrict flexibility of the shoe

Comfort features:

- · breathable yet waterproof
- thanks to GORE-TEX® lining, outstanding wearer comfort resulting from a newly developed last and climate-optimised, breathable materials
- · virtually seam-free construction made from high-tech microvelour material to eliminate pressure points
- · removable anti-static comfortable insole, with a moisture transport system and additional shock absorption around the heel and fore-
- · soft padding on collar and dust tongue
- · increased low-temperature flexibility of VIBRAM® rubber sole
- sizes 35 to 40 have been produced using a women's last

Areas of application:

moderate applications

uvex 2 GTX Vibram®	Shoe S3 WR HI HRO SRC			Lace-up boot S3 WR HI HRO SRC		
Art. no.	6526.1	6526.2	6526.3	6527.1	6527.2	6527.3
Width	10	11	12	10	11	12
Standard	EN ISO 20345:2011 S3 WR HI HRO SRC			EN ISO 20345:2011 S3 WR HI HRO SRC		
Upper	microvelour			microvelour		
Lining	GORE-TEX® laminate			GORE-TEX® laminate		
Sizes	35 to 52	35 to 52	35 to 52	35 to 52	35 to 52	35 to 52

