

Product data sheet flat fold mask FFP2 NR D, EN 149:2001 - uvex silv-Air 3200



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

Product features

- Particle-filtering flat fold mask without valve
- Protection level FFP2
- Soft material edges for high wearing comfort
- Continuous head band for a comfortable and secure fit
- Flexible and adjustable nose clip
- The masks are individually packed
- Soft sealing lip guarantees a secure, comfortable sealed position of the mask
- Compatible with uvex safety eyewear
- Mask fulfils the requirements of the dolomite dust test (D)

Materials

Headband: textile
Nose clip: PP
Headband clips: PP
Filter / mask: Melt Blown PP, Polyester
Sealing lip: EVA foam

Areas of use The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 10 times the respective limit values.	Mining, chemical industry, shipyards, iron and steel industry, woodworking, dust and fumes of substances such as asbestos, quartz, aluminum, copper, barium, titanium, vanadium, chrome, manganese and coal dust with more than 10% free silicon dioxide.
Weight	10 g
Standard	EN 149:2001+ A1:2009

Versions

Article number	Colour/Version	Retail unit
8733.200	Flat fold mask FFP2, white without valve	30 pieces per box
8753.200	Flat fold mask FFP2, white without valve	3 pieces in retail packaging