

Product data sheet flat fold mask FFP1 NR D, EN 149:2001 – uvex silv-Air 8113



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

<b>Product features</b>	<ul style="list-style-type: none"><li>• Particle-filtering flat fold mask with exhalation valve</li><li>• Protection level FFP 1</li><li>• Soft material edges for increased comfort</li><li>• Seamless, continuous headband for a comfortable, secure fit</li><li>• Integrated, flexible, adjustable nose clip</li><li>• Hydrophobic coating</li><li>• Foam pads at chin and nose area offers a perfect fit</li><li>• Exhalation valve for reduced build-up of heat and moisture inside the mask</li><li>• The masks are individually packed</li><li>• Mask fulfils the requirements of the dolomite dust test (D)</li></ul>
<b>Materials</b>	Headband: synthetic latex Nose clip: metal Sealing lip: synthetic foam Filter / mask: PP, Polyester Valve: PP

<p><b>Areas of use</b> The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to <b>4 times</b> the respective limit values.</p>	<p>Agriculture, food industry, quarries, cement plants, construction, softwood processing, dust and fumes of calcium carbonate, graphite, gypsum, chalk, cement, plaster, marble, zinc oxide, plant dust, cellulose, sulphur, cotton, ferrous metal respirable dust, coal dust with less than 10% free silicon oxide.</p>
<p><b>Weight</b></p>	<p>16 g</p>
<p><b>Standard</b></p>	<p>EN 149:2001+ A1:2009</p>

### Versions

Article number	Colour/Version	Retail unit
8708.113	Flat fold mask FFP1, silver with valve	15 pieces per box