

Product datasheet

uvex 3 quatro 6879 1-3

Safety boot DIN EN ISO 20345:2022+A1:2024 S3 FO CI SC SR Sizes: 36 - 52 | Width: 10, 11, 12











AREA OF APPLICATION

Heavy-duty applications place extensive demands on the safety shoe, its durability and stability due to external influences.

OUTSOLE

Dual-density polyurethane sole



- shock-absorbing and energy-returning uvex i-PUREnrj planet midsole with 10% recycled granulate from residues
- **bionom** x ergonomically designed PU outsole
- antistatic
- short-term heat-resistant up to 120°C
- cold-insulating (CI)
- excellent slip resistance (SR)
- oil- and fuel resistant (FO)
- free of silicones, plasticisers and other substances that interfere with wetting agents





FEATURES	
Upper material	hydrophobic leather
	water-repellent (WPA)
Lining material	textile distance mesh lining for comfortable foot climate (clima zone)
Fastening	• laces
Heel basket	 foamed heel basket out of PU for additional stability in the shoe
Reflecting elements	for increased visibility even in dark working environments
Comfort	soft padding on collar
	sizes 36-40 have been produced using a women's lastdust tongue
Innersole	removable comfortable innersole
PROTECTIVE FEATUR	FS
Toe cap	metal-free protective toe cap
Penetration resistance	steel penetration resistance
	•
Scuffcap	 out of PU for additional protection of the upper material (SC)
CEDTIFICATES	(30)
CERTIFICATES	
uvex medicare+	 certified for orthopaedic innersoles and shoe adjustments according to the description in DGUV 112- 191
ESD	 protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1
SUSTAINABILITY	
CO ₂ footprint	14.99 kg Cradle-to-Customer (calculation date 10/2025)
Recycled/sustainable materials	midsole, insole board and removable innersole made
,,	wholly or partly from recycled materials
	free from harmful substances in accordance with the uvex restricted substances list
ACCESORIES/ SPARE	PARTS
Replacement innersole	• 8693 7-9
Laces	black 9599922



Product datasheet

uvex 3 quatro 6881 1-3

Winter safety boot DIN EN ISO 20345:2022+A1:2024 S3 FO CI SC SR Sizes: 36 - 52 | Width: 10, 11, 12











AREA OF APPLICATION

Heavy-duty applications place extensive demands on the safety shoe, its durability and stability due to external influences.

OUTSOLE

Dual-density polyurethane sole



- shock-absorbing and energy-returning uvex i-PUREnrj planet midsole with 10% recycled granulate from residues
- bionom x ergonomically designed PU outsole
- antistatic
- short-term heat-resistant up to 120°C
- cold-insulating (CI)
- excellent slip resistance (SR)
- oil- and fuel resistant (FO)
- free of silicones, plasticisers and other substances that interfere with wetting agents





FEATURES	
Upper material	hydrophobic leather
	water-repellent (WPA)
Lining material	warm textile lining
Fastening	• laces
Heel basket	 foamed heel basket out of PU for additional stability in the shoe
Reflecting elements	for increased visibility even in dark working environments
Comfort	soft padding on collar
	sizes 36-40 have been produced using a women's lastdust tongue
Innersole	removable comfortable innersole
PROTECTIVE FEATUR	RES
Toe cap	metal-free protective toe cap
Penetration resistance	steel penetration resistance
Scuffcap	out of PU for additional protection of the upper material (SC)
CERTIFICATES	
uvex medicare+	certified for orthopaedic innersoles and shoe
	adjustments according to the description in DGUV 112- 191
ESD	 protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1
SUSTAINABILITY	
CO ₂ footprint	17.01 kg Cradle-to-Customer
·	(calculation date 10/2025)
Recycled/sustainable materials	midsole, insole board and removable innersole made
	 wholly or partly from recycled materials free from harmful substances in accordance with the
	tree from harmful substances in accordance with the uvex restricted substances list
ACCESORIES/ SPARE	
Replacement innersole	• 8693 7-9
Laces	black 9599925
<u> </u>	- Slack 555525



Product datasheet

uvex 3 quatro 6882 1-3

Winter safety boot DIN EN ISO 20345:2022+A1:2024 S3 FO CI SC SR Sizes: 36 - 52 | Width: 10, 11, 12















AREA OF APPLICATION

Heavy-duty applications place extensive demands on the safety shoe, its durability and stability due to external influences.

OUTSOLE

Dual-density polyurethane sole



- shock-absorbing and energy-returning uvex i-PUREnrj planet midsole with 10% recycled granulate from residues
- **bionom** x ergonomically designed PU outsole
- antistatic
- short-term heat-resistant up to 120°C
- cold-insulating (CI)
- excellent slip resistance (SR)
- oil- and fuel resistant (FO)
- free of silicones, plasticisers and other substances that interfere with wetting agents





FEATURES		
Upper material	hydrophobic leather	
	water-repellent (WPA)	
Lining material	warm textile lining	
Fastening	• zip	
Heel basket	foamed heel basket out of PU for additional stability in	
	the shoe	
Reflecting elements	for increased visibility even in dark working environments	
Comfort	soft padding on collar	
	sizes 36-40 have been produced using a women's last	
Innersole	removable comfortable innersole	
PROTECTIVE FEATUR	RES	
Toe cap	metal-free protective toe cap	
Penetration resistance	steel penetration resistance	
Scuffcap	out of PU for additional protection of the upper material	
·	(SC)	
CERTIFICATES		
uvex medicare+	certified for orthopaedic innersoles and shoe	
	adjustments according to the description in DGUV 112-	
	191	
ESD	protection against electrostatic charge according to EN	
	61340-4-3 und EN 61340-5-1	
SUSTAINABILITY		
CO ₂ footprint	22.79 kg Cradle-to-Customer	
	(calculation date 10/2025)	
Recycled/sustainable materials	midsole, insole board and removable innersole made wholly or partly from recycled metarials.	
	 wholly or partly from recycled materials free from harmful substances in accordance with the 	
	uvex restricted substances list	
ACCESORIES/ SPARE PARTS		
Replacement innersole	• 8693 7-9	
. iopiacomont imicroole	33373	